

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1239575S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

BASIX

Date of issue: Wednesday, 15 September 2021

To be valid, this certificate must be lodged within 3 months of the date of issue.



Project summary	
Project name	Carr - Unit 2
Street address	31 Court Street Mudgee 2850
Local Government Area	Mid-Western Regional Council
Plan type and plan number	deposited 758721
Lot no.	15
Section no.	-
Project type	separate dwelling house
No. of bedrooms	3
Project score	
Water	✓ 33 Target 30
Thermal Comfort	✓ Pass Target Pass
Energy	✓ 61 Target 40

Certificate Prepared by

Name / Company Name: Rohrs Refrigeration

ABN (if applicable): 37 101 256 320

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_18_5 Certificate No.: 1239575S Wednesday, 15 September 2021 page 1/9

Description of project

BASIX

Project address	
Project name	Carr - Unit 2
Street address	31 Court Street Mudgee 2850
Local Government Area	Mid-Western Regional Council
Plan type and plan number	Deposited Plan 758721
Lot no.	15
Section no.	-
Project type	
Project type	separate dwelling house
No. of bedrooms	3
Site details	
Site area (m²)	433
Roof area (m²)	288
Conditioned floor area (m2)	161.0
Unconditioned floor area (m2)	16.0
Total area of garden and lawn (m2)	70

Assessor details and thermal lo	pads	
Assessor number	n/a	
Certificate number	n/a	
Climate zone	n/a	
Area adjusted cooling load (MJ/m².year)	n/a	
Area adjusted heating load (MJ/m².year)	n/a	
Ceiling fan in at least one bedroom	n/a	
Ceiling fan in at least one living room or other conditioned area	n/a	
Project score		
Water	✓ 33	Target 30
Thermal Comfort	✓ Pass	Target Pass
Energy	✓ 61	Target 40

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_18_5 Certificate No.: 1239575S Wednesday, 15 September 2021 page 2/9

Schedule of BASIX commitments

BASIX

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Fixtures			
The applicant must install showerheads with a minimum rating of 3 star (> 4.5 but <= 6 L/min) in all showers in the development.		→	V
The applicant must install a toilet flushing system with a minimum rating of 3 star in each toilet in the development.		~	V
The applicant must install taps with a minimum rating of 3 star in the kitchen in the development.		~	
The applicant must install basin taps with a minimum rating of 3 star in each bathroom in the development.		~	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 2000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	~	~	V
The applicant must configure the rainwater tank to collect rain runoff from at least 288 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		~	V
The applicant must connect the rainwater tank to:			
 at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 		~	V

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_18_5 Certificate No.: 1239575S Wednesday, 15 September 2021 page 3/9

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	V	~	-
The conditioned floor area of the dwelling must not exceed 300 square metres.	~	V	V
The dwelling must not contain open mezzanine area exceeding 25 square metres.	V	V	V
The dwelling must not contain third level habitable attic room.	V	~	-
Floor, walls and ceiling/roof	1		<u>'</u>
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	~	<u> </u>	V

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground	1 (slab edge)	in-slab heating system
external wall - brick veneer	2.06 (or 2.60 including construction)	
internal wall shared with garage - plasterboard	nil	
ceiling and roof - flat ceiling / pitched roof	ceiling: 3.25 (up), roof: foil/sarking	unventilated; light (solar absorptance < 0.475)

Note	Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.
Note	• In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_18_5 Certificate No.: 1239575S Wednesday, 15 September 2021 page 4/9

BASIX

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Windows, glazed doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	-	→	-
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.		~	~
The following requirements must also be satisfied in relation to each window and glazed door:		<u> </u>	~
• For the following glass and frame types, the certifier check can be performed by visual inspection.			V
- Aluminium single clear			
- Aluminium double (air) clear			
- Timber/uPVC/fibreglass single clear			
- Timber/uPVC/fibreglass double (air) clear			
 Overshadowing buildings/vegetation must be of the height and distance from the centre and the base of the window and glazed door, as specified in the 'overshadowing' column. 	-	•	-

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
North facing					
Bed 1	1800	750	timber/UPVC/fibreglass, single, clear	verandah 1800 mm, 2100 mm above base of window or glazed door	not overshadowed
Family	1800	900	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
Hall	2400	3600	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
ENS	1800	600	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
Family	1800	900	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
Bed 1	1800	750	timber/UPVC/fibreglass, single, clear	verandah 1800 mm, 2100 mm above base of window or glazed door	not overshadowed

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_18_5 Certificate No.: 1239575S Wednesday, 15 September 2021 page 5/9

BASIX

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
East facing					
WIR	1800	600	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
Hall	1800	600	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
Bed 3	1800	600	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
Bed 3	1800	600	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
Family	2400	3000	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	2-4 m high, 2-5 m away
South facing					
Laundry	600	1800	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
Bed 2	600	2400	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	2-4 m high, 2 m away
Sitting	600	2400	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
BAth	600	1800	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	2-4 m high, 2 m away
Pantry	600	900	timber/UPVC/fibreglass, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_18_5 Certificate No.: 1239575S Wednesday, 15 September 2021 page 6/9

BASIX

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: electric storage.	V	→	V
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 3-phase airconditioning; Energy rating: EER 2.5 - 3.0		~	~
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: 3-phase airconditioning; Energy rating: EER 2.5 - 3.0		~	V
The cooling system must provide for day/night zoning between living areas and bedrooms.		•	V
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 3-phase airconditioning; Energy rating: EER 2.5 - 3.0		~	~
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 bedroom: 3-phase airconditioning; Energy rating: EER 2.5 - 3.0		~	~
The heating system must provide for day/night zoning between living areas and bedrooms.		•	V
Ventilation			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, not ducted; Operation control: manual switch on/off		•	V
Kitchen: individual fan, ducted to façade or roof; Operation control: manual switch on/off		~	•
Laundry: natural ventilation only, or no laundry; Operation control: n/a		V	•
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps:			
• at least 3 of the bedrooms / study;			

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_18_5 Certificate No.: 1239575S Wednesday, 15 September 2021 page 7/9

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
at least 1 of the living / dining rooms;		~	~
• the kitchen;		V	-
all bathrooms/toilets;			
• the laundry;			
• all hallways;			
Natural lighting			'
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	~	~	-
The applicant must install a window and/or skylight in 2 bathroom(s)/toilet(s) in the development for natural lighting.		~	~
Alternative energy			
The applicant must install a photovoltaic system with the capacity to generate at least 3 peak kilowatts of electricity as part of the development. The applicant must connect this system to the development's electrical system.	~	→	~
Other			
The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions.		•	
The applicant must install a fixed outdoor clothes drying line as part of the development.			

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_18_5 Certificate No.: 1239575S Wednesday, 15 September 2021 page 8/9

Legend

BASIX

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate(either interim or final) for the development may be issued.

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_18_5 Certificate No.: 1239575S Wednesday, 15 September 2021 page 9/9